2019 -- H 5667

LC001761

STATE OF RHODE ISLAND

IN GENERAL ASSEMBLY

JANUARY SESSION, A.D. 2019

AN ACT

RELATING TO PUBLIC UTILITIES AND CARRIERS -- THE ENERGY AND CONSUMER SAVINGS ACT OF 2005

Introduced By: Representatives Bennett, Edwards, Jacquard, and Diaz

Date Introduced: February 27, 2019

Referred To: House Environment and Natural Resources

It is enacted by the General Assembly as follows:

1 SECTION 1. Sections 39-27-2, 39-27-3, 39-27-4, 39-27-5, 39-27-6, 39-27-7 and 39-27-8
2 of the General Laws in Chapter 39-27 entitled "The Energy and Consumer Savings Act of 2005"

are hereby amended to read as follows:

<u>39-27-2. Findings.</u>

3

4

5

6

7

8

9

10

11

12

13

14

15

16

The legislature finds that:

(a) Efficiency standards for certain products sold or installed in the state assure consumers and businesses that such products meet minimum efficiency performance levels, thus reducing energy and water waste and saving consumers and businesses money on utility bills.

(b) Such efficiency standards save energy and thus reduce pollution and other environmental impacts associated with the production, distribution and use of electricity, and natural gas and other fuels.

(c) Such efficiency standards can make electricity <u>and natural gas</u> systems more reliable by reducing the strain on <u>the electricity grid systems</u> during peak demand periods. Furthermore, improved energy efficiency can reduce or delay the need for new power plants, power transmission lines, and power distribution system upgrades <u>as well as new and expanded gas pipelines</u>.

17 (d) Energy efficiency Efficiency standards contribute to the economy of this state by
18 helping to better balance energy supply and demand for both water and energy, thus reducing

1	pressure for that creates higher natural gas, water and electricity prices. By saving consumers and
2	businesses money on energy utility bills, efficiency standards help the state and local economy,
3	since energy utility bill savings can be spent on local goods and services.
4	(e) Furthermore, such water efficiency standards save water and thus reduce the strain on
5	the water supply. Furthermore, improved water efficiency can reduce or delay the need for water
6	and sewer infrastructure improvements.
7	<u>39-27-3. Definitions.</u>
8	As used in this chapter:
9	(a) "Automatic commercial ice-maker" means a factory-made assembly that is shipped in
10	one or more packages that consists of a condensing unit and ice making section operating as an
11	integrated unit, that makes and harvests ice cubes, and that may store and dispense ice. This term
12	includes machines with capacities between and including fifty (50) and two thousand five
13	hundred (2,500) pounds per twenty four (24) hours.
14	(b) "Ballast" means a device used with an electric discharge lamp to obtain necessary
15	circuit conditions (voltage, current and waveform) for starting and operating the lamp.
16	(c) "Boiler" means a self-contained low-pressure appliance for supplying steam or hot
17	water primarily designed for space heating.
18	(d) "Bottle type water dispenser" means a water dispenser that uses a bottle or reservoir
19	as the source of potable water.
20	(e) "Chief of Energy and Community Services" means the head official of the Rhode
21	Island state energy office.
22	(f) "Commercial clothes washer" means a soft mount horizontal or vertical-axis clothes
23	washer that:
24	(1) Has a clothes container compartment no greater than three and a half (3.5) cubic feet
25	in the case of a horizontal axis product or no greater than four (4.0) cubic feet in the case of a
26	vertical axis product; and
27	(2) Is designed for use by more than one household, such as in multi-family housing,
28	apartments or coin laundries.
29	(g) "Commercial hot food holding cabinet" means an appliance that is a heated, fully-
30	enclosed compartment with one or more solid doors, and that is designed to maintain the
31	temperature of hot food that has been cooked in a separate appliance. "Commercial hot food
32	holding cabinet" does not include heated glass merchandizing cabinets, drawer warmers, or cook-
33	and hold appliances.
34	(h) "Commercial pre-rinse spray valve" means a hand-held device designed and marketed

1	for use with commercial dishwashing and ware washing equipment and which sprays water on
2	dishes, flatware, and other food service items for the purpose of removing food residue prior to
3	their cleaning.
4	(i) "Commercial refrigerator, freezer and refrigerator-freezer" means self-contained
5	refrigeration equipment that:
6	(1) Is not a consumer product as regulated pursuant to 42 U.S.C. § 6291 and subsequent
7	sections;
8	(2) Operates at a chilled, frozen, combination chilled/frozen, or variable temperature for
9	the purpose of storing and/or merchandising food, beverages and/or ice;
10	(3) May have transparent and/or solid hinged doors, sliding doors, or a combination of
11	hinged and sliding doors; and
12	(4) Incorporates most components involved in the vapor compression cycle and the
13	refrigerated compartment in a single cabinet.
14	This term does not include:
15	(1) Units with eighty-five (85) cubic feet or more of internal volume;
16	(2) Walk in refrigerators or freezers;
17	(3) Units with no doors; or
18	(4) Freezers specifically designed for ice cream.
19	(j) "Commission" means the Rhode Island public utilities commission.
20	(k) "Compensation" means money or any other valuable thing, regardless of form,
21	received or to be received by a person for services rendered.
22	(l) "Electricity ratio" is the ratio of furnace electricity use to total furnace energy use.
23	$\underline{Electricity\ ratio} = (3.412*EAE/(1000*Ef + 3.412*EAE))\ where\ EAE\ (average\ annual\ auxiliary)$
24	electrical consumption) and EF (average annual fuel energy consumption) are defined in
25	Appendix N to subpart B of part 430 of title 10 of the Code of Federal Regulations.
26	(m) "High intensity discharge lamp" means a lamp in which light is produced by the
27	passage of an electric current through a vapor or gas, and in which the light-producing are is
28	stabilized by bulb wall temperature and the arc tube has a bulb wall loading in excess of three (3)
29	watts per square centimeter.
30	(n) "Illuminated exit sign" means an internally-illuminated sign that is designed to be
31	permanently fixed in place to identify a building exit and consists of an electrically powered
32	integral light source that illuminates the legend "EXIT" and any directional indicators and
33	provides contrast between the legend, any directional indicators and the background.
34	(o) "Large packaged air conditioning equipment" means electronically operated, air-

1	cooled an conditioning and an conditioning near pump equipment having cooling capacity
2	greater than or equal to two hundred forty thousand (240,000) Btu/hour but less than seven
3	hundred sixty thousand (760,000) Btu/hour that is built as a package and shipped as a whole to
4	end-user sites.
5	(p) "Low voltage dry-type distribution transformer" means a transformer that:
6	(1) Has an input voltage of six hundred (600) volts or less;
7	(2) Is air-cooled;
8	(3) Does not use oil as a coolant; and
9	(4) Is rated for operation at a frequency of sixty (60) Hertz.
10	(q) "Mercury vapor lamp" means a high intensity discharge lamp in which the major
11	portion of the light is produced by radiation from mercury operating at a partial pressure in excess
12	of one hundred thousand (100,000) PA (approximately 1 atm). This includes clear, phosphor-
13	coated and self-ballasted lamps.
14	(r) "Metal halide lamp" means a high intensity discharge lamp in which the major portion
15	of the light is produced by radiation of metal halides and their products of dissociation, possibly
16	in combination with metallic vapors.
17	(s) "Metal halide lamp fixture" means a lamp fixture designed to be operated with a metal
18	halide lamp and a ballast for a metal halide lamp.
19	(t) "Probe start metal halide ballast" means a ballast used to operate metal halide lamps
20	which does not contain an igniter and which instead starts lamps by using a third staring electrode
21	"probe" in the arc tube.
22	(u) "Pulldown refrigerator" means a commercial refrigerator with doors that, when fully
23	loaded with twelve (12) ounce canned beverages at ninety (90) degrees F, can cool these
24	beverages to an average stable temperature of thirty eight (38) degrees F in twelve (12) hours or
25	less.
26	(v) "Residential boiler" means a self-contained appliance for supplying steam or hot
27	water, which uses natural gas, propane, or home heating oil, and which has a heat input rate of
28	less than three hundred thousand (300,000) Btu per hour.
29	(w) "Residential furnace" means a self-contained space heater designed to supply heated
30	air through ducts of more than ten (10) inches length and which utilizes only single phase electric
31	current, or single phase electric current or DC current in conjunction with natural gas, propane, or
32	home heating oil, and which:
33	(1) Is designed to be the principle heating source for the living space of one or more
34	residences:

1	(2) is not contained within the same caomet with a central an conditioner whose fated
2	cooling capacity is above sixty-five thousand (65,000) Btu per hour; and
3	(3) Has a heat input rate of less than two hundred twenty-five thousand (225,000) Btu per
4	hour.
5	(x) "Single voltage external AC to DC power supply" means a device that:
6	(1) Is designed to convert line voltage AC input into lower voltage DC output;
7	(2) Is able to convert to one DC output voltage at a time;
8	(3) Is sold with, or intended to be used with, a separate end use product that constitutes
9	the primary power load;
10	(4) Is contained within a separate physical enclosure from the end-use product;
11	(5) Is connected to the end-use product via a removable or hard-wired male/female
12	electrical connection, cable, cord or other wiring;
13	(6) Does not have batteries or battery packs, including those that are removable, that
14	physically attach directly to the power supply unit;
15	(7) Does not have a battery chemistry or type selector switch and indicator light; or
16	(8) Has a nameplate output power less than or equal to two hundred fifty (250) watts.
17	(y) "State regulated incandescent reflector lamp" means a lamp, not colored or designed
18	for rough or vibration service applications, with an inner reflective coating on the outer bulb to
19	direct the light, an E26 medium screw base, a rated voltage or voltage range that lies at least
20	partially within one hundred fifteen (115) to one hundred thirty (130) volts, and that falls into
21	either of the following categories: a blown PAR (BPAR), bulged reflector (BR), or elliptical
22	reflector (ER) bulb shape or similar bulb shape with a diameter equal to or greater than two and
23	one quarter (2.25) inches; or a reflector (R), parabolic aluminized reflector (PARA) bulged
24	reflector (BR) or similar bulb shape with a diameter of two and one quarter (2.25) to two and
25	three quarter (2.75) inches, inclusive.
26	(z) "Torchiere" means a portable electric lighting fixture with a reflective bowl that
27	directs light upward onto a ceiling so as to produce indirect illumination on the surfaces below. A
28	torchiere may include downward directed lamps in addition to the upward, indirect illumination.
29	(aa) "Traffic signal module" means a standard eight (8) inch (two hundred millimeter
30	(200 mm)) or twelve (12) inch (three hundred millimeter (300 mm)) traffic signal indication,
31	consisting of a light source, a lens, and all other parts necessary for operation.
32	(bb) "Transformer" means a device consisting of two (2) or more coils of insulated wire
33	and that is designed to transfer alternating current by electromagnetic induction from one coil to
2/1	another to shange the original voltage or gurrent value. The term "transformer" does not include:

1	(1) Fransiormers with multiple voltage taps, with the nighest voltage tap equaling at least
2	twenty percent (20%) more than the lowest voltage tap; or
3	(2) Transformers, such as those commonly known as drive transformers, rectifier
4	transformers, auto-transformers, uninterruptible power system transformers, impedance
5	transformers, regulating transformers, sealed and nonventilating transformers, machine tool
6	transformers, welding transformers, grounding transformers, or testing transformers, that are
7	designed to be used in a special purpose application and are unlikely to be used in general
8	purpose applications.
9	(cc) "Unit heater" means a self-contained, vented fan-type commercial space heater that
10	uses natural gas or propane, and that is designed to be installed without ducts within a heated
11	space, except that such term does not include any products covered by federal standards
12	established pursuant to 42 U.S.C. § 6291 and subsequent sections or any product that is a direct
13	vent, forced flue heater with a sealed combustion burner.
14	(dd) "Walk in refrigerator" and "walk in freezer" mean a space, designed for the purpose
15	of storing and/or merchandising food, beverages and/or ice, that is refrigerated to temperatures,
16	respectively, at or above and below thirty-two (32) degrees F that can be walked into.
17	(ee) "Water dispenser" means a factory-made assembly that mechanically cools and heats
18	potable water and that dispenses the cooled or heated water by integral or remote means.
19	(1) The following definitions refer to air compressors:
20	(i) "Air compressor" means a compressor designed to compress air that has an inlet open
21	to the atmosphere or other source of air, and is made up of a compression element (bare
22	compressor), driver(s), mechanical equipment to drive the compressor element, and any ancillary
23	equipment.
24	(ii) "Compressor" means a machine or apparatus that converts different types of energy
25	into the potential energy of gas pressure for displacement and compression of gaseous media to
26	any higher-pressure values above atmospheric pressure and has a pressure ratio at full-load
27	operating pressure greater than 1.3.
28	(2) "Bottle-type water dispenser" means a water dispenser that uses a bottle or reservoir
29	as the source of potable water.
30	(3) "Commercial dishwasher" means a machine designed to clean and sanitize plates,
31	pots, pans, glasses, cups, bowls, utensils, and trays by applying sprays of detergent solution (with
32	or without blasting media granules) and a sanitizing rinse.
33	(4) "Commercial fryer" means an appliance, including a cooking vessel, in which oil is
34	placed to such a depth that the cooking food is essentially supported by displacement of the

1	cooking fluid rather than by the bottom of the vessel. Heat is delivered to the cooking fluid by
2	means of an immersed electric element of band-wrapped vessel (electric fryers) or by heat
3	transfer from gas burners through either the walls of the fryer or through tubes passing through
4	the cooking fluid (gas fryers).
5	(5) "Commercial hot-food holding cabinet" means a heated, fully enclosed compartment
6	with one or more solid transparent doors designed to maintain the temperature of hot food that
7	has been cooked using a separate appliance. "Commercial hot-food holding cabinet" does not
8	include heated glass merchandizing cabinets, drawer warmers, or cook-and-hold appliances.
9	(6) "Commercial steam cooker," also known as a "compartment steamer," means a device
10	with one or more food-steaming compartments in which the energy in the steam is transferred to
11	the food by direct contact. Models may include countertop models, wall-mounted models, and
12	floor models mounted on a stand, pedestal, or cabinet-style base.
13	(7) "Commission" means the Rhode Island public utilities commission.
14	(8) "Commissioner" means the commissioner of the office of energy resources.
15	(9 "Compensation" means money or any other thing of value, regardless of form,
16	received or to be received by a person for services rendered.
17	(10) "General service lamp" means a lamp that has an American National Standards
18	Institute (ANSI) base; is able to operate at a voltage of twelve (12) volts or twenty-four (24) volts,
19	at or between one hundred (100) to one hundred thirty (130) volts, at or between two hundred
20	twenty (220) to two hundred forty (240) volts, or of two hundred seventy-seven (277) volts for
21	integrated lamps, or is able to operate at any voltage for non-integrated lamps; has an initial
22	lumen output of greater than or equal to three hundred ten (310) lumens (or two hundred thirty-
23	two (232) lumens for modified spectrum general service incandescent lamps) and less than or
24	equal to three thousand three hundred (3,300) lumens; is not a light fixture; is not an LED
25	downlight retrofit kit; and is used in general lighting applications. General service lamps include,
26	but are not limited to, general service incandescent lamps, compact fluorescent lamps, general
27	service light-emitting diode lamps, and general service organic light-emitting diode lamps.
28	General service lamps do not include:
29	(i) Appliance lamps;
30	(ii) Black light lamps;
31	(iii) Bug lamps;
32	(iv) Colored lamps;
33	(v) G shape lamps with a diameter of five inches (5") or more as defined in ANSI C79.1-
34	2002•

1	(vi) General service fluorescent lamps;
2	(vii) High-intensity discharge lamps;
3	(viii) Infrared lamps;
4	(ix) J, JC, JCD, JCS, JCV, JCX, JD, JS, and JT shape lamps that do not have Edison
5	screw bases;
6	(x) Lamps that have a wedge base or prefocus base;
7	(xi) Left-hand thread lamps;
8	(xii) Marine lamps;
9	(xiii) Marine signal service lamps;
10	(xiv) Mine service lamps;
11	(xv) MR shape lamps that have a first number symbol equal to sixteen (16) (diameter
12	equal to two inches (2")) as defined in ANSI C79.1-2002, operate at twelve (12) volts, and have a
13	lumen output greater than or equal to eight hundred (800);
14	(xvi) Other fluorescent lamps;
15	(xvii) Plant light lamps;
16	(xviii) R20 short lamps;
17	(xix) Reflector lamps that have a first number symbol less than sixteen (16) (diameter
18	less than two inches (2")) as defined in ANSI C79.1-2002 and that do not have E26/E24, E26d,
19	E26/50x39, E26/53x39, E29/28, E29/53x39, E39, E39d, EP39, or EX39 bases;
20	(xx) S shape or G shape lamps that have a first number symbol less than or equal to 12.5
21	(diameter less than or equal to 1.5625 inches) as defined in ANSI C79.1-2002;
22	(xxi) Sign service lamps;
23	(xxii) Silver bowl lamps;
24	(xxiii) Showcase lamps;
25	(xxiv) Specialty MR lamps;
26	(xxv) T shape lamps that have a first number symbol less than or equal to eight (8)
27	(diameter less than or equal to one inch (1")) as defined in ANSI C79.1-2002, nominal overall
28	length less than twelve inches (12"), and that are not compact fluorescent lamps (as defined in
29	this section); and
30	(xxvi) Traffic signal lamps.
31	(11) "High color rendering index (CRI) fluorescent lamp" means a fluorescent lamp with
32	a color-rendering index of eighty-seven (87) or greater that is not a compact fluorescent lamp.
33	(12) The following definitions refer to faucets and showerheads:
34	(i) "Faucet" means a lavatory faucet, kitchen faucet, metering faucet, public lavatory

1	faucet, or replacement aerator for a lavatory, public lavatory or kitchen faucet.
2	(ii) "Public lavatory faucet" means a fitting intended to be installed in nonresidential
3	bathrooms that are exposed to walk-in traffic.
4	(iii) "Metering faucet" means a faucet fitting that, when turned on, will gradually shut
5	itself off over a period of several seconds.
6	(iv) "Replacement aerator" means an aerator sold as a replacement, separate from the
7	faucet to which it is intended to be attached.
8	(v) "Showerhead" means a device through which water is discharged for a shower bath
9	and includes a handheld showerhead but does not include a safety shower showerhead, an
10	accessory to a supply fitting for spraying water onto the bather, typically from an overhead
11	position. The term includes a body spray and handheld shower.
12	(vi) "Body spray" means a shower device for spraying water onto a bather other than
13	from the overhead position.
14	(vii) "Handheld shower" means a showerhead that can be held or fixed in place for the
15	purpose of spraying water onto a bather and that is connected to a flexible hose.
16	(13) The following definitions refer to urinals and water closets:
17	(i) "Plumbing fixture" means an exchangeable device, which connects to a plumbing
18	system to deliver and drain away water and waste.
19	(ii) "Urinal" means a plumbing fixture that receives only liquid body waste and, on
20	demand, conveys the waste through a trap into a drainage system.
21	(iii) "Water closet" means a plumbing fixture having a water-containing receptor that
22	receives liquid and solid body waste through an exposed integral trap into a drainage system.
23	(iv) "Dual-flush effective flush volume" means the average flush volume of two (2)
24	reduced flushes and one full flush.
25	(v) "Dual-flush water closet" means a water closet incorporating a feature that allows the
26	user to flush the water closet with either a reduced or a full volume of water.
27	(vi) "Trough-type urinal" means a urinal designed for simultaneous use by two (2) or
28	more persons.
29	(14) The following definitions refer to portable air conditioners:
30	(i) "Portable air conditioner" means a portable encased assembly, other than a packaged
31	terminal air conditioner, room air conditioner, or dehumidifier, that delivers cooled, conditioned
32	air to an enclosed space, and is powered by single-phase electric current. It includes a source of
33	refrigeration and may include additional means for air circulation and heating and may be a
34	single-duct or a dual-duct portable air conditioner.

1	(ii) "Single-duct portable air conditioner" means a portable air conditioner that draws all
2	of the condenser inlet air from the conditioned space without the means of a duct and discharges
3	the condenser outlet air outside the conditioned space through a single duct attached to an
4	adjustable window bracket.
5	(iii) "Dual-duct portable air conditioner" means a portable air conditioner that draws
6	some or all of the condenser inlet air from outside the conditioned space through a duct attached
7	to an adjustable window bracket, may draw additional condenser inlet air from the conditioned
8	space, and discharges the condenser outlet air outside the conditioned space by means of a
9	separate duct attached to an adjustable window bracket.
10	(15) "Portable electric spa" means a factory-built electric spa or hot tub which may or
11	may not include any combination of integral controls, water heating or water circulating
12	equipment.
13	(16) "Residential furnace" means a self-contained space heater designed to supply heated
14	air through ducts of more than ten inches (10") in length and which utilizes only single-phase
15	electric current, or DC current in conjunction with natural gas, propane, or home heating oil, and
16	which:
17	(i) Is designed to be the principle heating source for the living space of one or more
18	residences;
19	(ii) Is not contained within the same cabinet with a central air conditioner whose rated
20	cooling capacity is above sixty-five thousand (65,000) Btu per hour; and
21	(iii) Has a heat input rate of less than two hundred twenty-five thousand (225,000) Btu
22	per hour.
23	(17) "Residential ventilating fan" means a ceiling, wall-mounted, or remotely mounted
24	in-line fan designed to be used in a bathroom or utility room, whose purpose is to move air from
25	inside the building to the outdoors.
26	(18) The following definitions refer to spray sprinkler bodies:
27	(i) "Pressure regulator" means a device that maintains constant operating pressure
28	immediately downstream from the device, given higher pressure upstream.
29	(ii) "Spray sprinkler body" means the exterior case or shell of a sprinkler incorporating a
30	means of connection to the piping system designed to convey water to a nozzle or orifice.
31	(19) "Uninterruptible power supply" means a battery charger consisting of a combination
32	of convertors, switches and energy storage devices (such as batteries), constituting a power
33	system for maintaining continuity of load power in case of input power failure.
34	(20) The following definitions refer to water coolers:

1	(i) water cooler means a neestanding device that consumes energy to cool of near
2	potable water.
3	(ii) "Cold only units" dispense cold water only.
4	(iii) "Hot and cold units" dispense both hot and cold water. Some units also offer room-
5	temperature water.
6	(iv) Cook and cold units" dispense both cold and room temperature water.
7	(v) "Storage-type" means thermally conditioned water is stored in a tank in the water
8	cooler and is available instantaneously. Point-of-use, dry storage compartment, and bottled water
9	coolers are included in this category.
10	(vi) "On demand" means the water cooler heats water as it is requested, which typically
11	takes a few minutes to deliver.
12	<u>39-27-4. Scope.</u>
13	(a) The provisions of this chapter apply to the following types of new products sold,
14	offered for sale or installed in the state:
15	(1) Automatic commercial ice makers Air compressors;
16	(2) Commercial clothes washers;
17	(3) Commercial pre-rinse spray valves;
18	(4)(2) Commercial refrigerators, freezers, and refrigerator freezers Commercial
19	<u>dishwashers</u> ;
20	(5)(3) High intensity discharge lamp ballasts Commercial fryers;
21	(6)(4) Illuminated exit signs Commercial steam cookers;
22	(7)(5) Large packaged air-conditioning equipment Computers and computer monitors;
23	(8)(6) Low voltage dry type distribution transformers Faucets;
24	(9)(7) Metal halide lamp fixtures General service lamps;
25	(10)(8) Single voltage external AC to DC power supplies High CRI fluorescent lamps;
26	(11)(9) Torchieres Portable air conditioners;
27	(12)(10) Traffic signal modules Portable electric spas;
28	(13)(11) Unit heaters Residential ventilating fans.
29	(12) Showerheads;
30	(13) Spray sprinkler bodies;
31	(14) Uninterruptible power supplies;
32	(15) Urinals;
33	(16) Water closets;
34	(17) Water coolers; and

1	(18) Any other products as may be designated by the commissioner in accordance with §
2	39-27-7 or by operation of law.
3	(b) The provisions of this chapter also apply to the following types of new products sold,
4	offered for sale or installed in the state:
5	(1) Bottle-type water dispensers;
6	(2) Commercial hot food holding cabinets; and
7	(3) Residential boilers and residential furnaces;
8	(4) State regulated incandescent reflector lamps; and
9	(5) Walk-in refrigerators and walk-in freezers.
10	(c) The provisions of this chapter do not apply to:
11	(1) New products manufactured in the state and sold outside the state;
12	(2) New products manufactured outside the state and sold at wholesale inside the state for
13	final retail sale and installation outside the state;
14	(3) Products installed in mobile manufactured homes at the time of construction; or
15	(4) Products designed expressly for installation and use in recreational vehicles.
16	39-27-5. Efficiency standards.
17	(a) Not later than June 1, 2006, the commission, in consultation with the state building
18	commissioner and the chief of energy and community services, shall adopt regulations, in
19	accordance with the provisions of chapter 35 of title 42, establishing minimum efficiency
20	standards for the types of new products set forth in subparagraph (a) of § 39-27-4. The
21	regulations shall provide for the following minimum efficiency standards:
22	(1) Automatic commercial ice makers shall meet the energy efficiency requirements
23	shown in table A 7 of § 1605.3 of the California Code of Regulations, Title 20: Division 2,
24	Chapter 4, Article 4: Appliance Efficiency Regulations as adopted on December 15, 2004.
25	(2) Commercial clothes washers shall meet the requirements shown in Table P-4 of §
26	1605.3 of the California Code of Regulations, Title 20: Division 2, Chapter 4, Article 4:
27	Appliance Efficiency Regulations in effect on December 15, 2004.
28	(3) Commercial pre-rinse spray valves shall have a flow rate equal to or less than one and
29	six tenths (1.6) gallons per minute.
30	(4) Commercial refrigerators, freezers and refrigerator freezers shall meet the minimum
31	efficiency requirements shown in Table A 6 of § 1605.3 of the California Code of Regulations,
32	Title 20: Division 2, Chapter 4, Article 4: Appliance Efficiency Regulations as adopted on
33	December 15, 2004, except that pulldown refrigerators with transparent doors shall meet a
21	requirement five persont (50/) less stringent then shown in the Colifornia regulations

•	(5) Then menorly discharge tamp outlasts shart not be designed and marketed to operate
2	a mercury vapor lamp.
3	(6) Illuminated exit signs shall have an input power demand of five (5) watts or less per
4	illuminated face.
5	(7) Large packaged air conditioning equipment shall meet a minimum energy efficiency
6	ratio of:
7	(i) Ten (10.0) for air conditioning without an integrated heating component or with
8	electric resistance heating integrated into the unit;
9	(ii) Nine and eight tenths (9.8) for air conditioning with heating other than electric
10	resistance integrated into the unit;
1	(iii) Nine and five tenths (9.5) for air conditioning with heating other than electric
12	resistance integrated heating component or with electric resistance heating integrated into the
13	unit;
14	(iv) Nine and three tenths (9.3) for air conditioning heat pump equipment with heating
15	other than electric resistance integrated into the unit. Large packaged air conditioning heat pumps
16	shall meet a minimum coefficient of performance in the heating mode of three and two tenths
17	(3.2) (measured at a high temperature rating of forty seven (47) degrees F db).
18	(8) Low voltage dry type distribution transformers shall meet the Class 1 efficiency
19	levels for low voltage distribution transformers specified in Table 4-2 of the "Guide for
20	Determining Energy Efficiency for Distribution Transformers" published by the National
21	Electrical Manufacturers Association (NEMA Standard TP 1-2002).
22	(9) Metal halide lamp fixtures that operate in a vertical position and are designed to be
23	operated with lamps rated greater than or equal to one hundred fifty (150) watts but less than or
24	equal to five hundred (500) watts shall not contain a probe-start metal halide lamp ballast.
25	(10) Single voltage external AC to DC power supplies shall meet the tier one energy
26	efficiency requirements shown in Table U-1 of § 1605.3 of the California Code of Regulations,
27	Title 20: Division 2, Chapter 4, Article 4: Appliance Efficiency Regulations as adopted on
28	December 15, 2004. This standard applies to single voltage AC to DC power supplies that are
29	sold individually and to those that are sold as a component of or in conjunction with another
30	product. Single voltage external AC to DC power supplies that are made available by a product
31	manufacturer as service parts or spare parts for its products manufactured prior to January 1, 2008
32	shall be exempt from this provision.
33	(11) Torchieres shall not use more than one hundred ninety (190) watts. A torchiere shall
34	be deemed to use more than one hundred ninety (190) watts if any commercially available lamp

1	or combination of lamps can be inserted in	n its socket(s) and cause the torc	hiere to draw more than
2	one hundred ninety (190) watts when ope	rated at full brightness.	
3	(12) Traffic signal modules sha	ill meet the product specification	on of the "Energy Star
4	Program Requirements for Traffic Sign	als" developed by the U.S. En	vironmental Protection
5	Agency that took effect in February 200	1 and shall be installed with cor	mpatible, electronically-
6	connected signal control interface devices	s and conflict monitoring systems	}.
7	(13) Unit heater shall be equipp	ped with an intermittent ignition	device and shall have
8	either power venting or an automatic flue	damper.	
9	(b)(a) Not later than June 1, 2007	, the commission, in consultation	n with the state building
10	commissioner and the chief of energy	and community services, shall	l adopt regulations, in
11	accordance with the provisions of chapte	er 42-35, establishing minimum	efficiency standards for
12	the types of new products set forth in paragraph (b) of § 39-27-4. The regulations shall provide		egulations shall provide
13	for the following minimum efficiency sta	ndards.	
14	(1) Bottle-type water dispensers of	designed for dispensing both hot	and cold water shall not
15	have standby energy consumption greater	than one and two tenths (1.2) kil	lowatt-hours per day.
16	(2) Commercial hot food holding	cabinets shall have a maximum	idle energy rate of forty
17	(40) watts per cubic foot of interior volun	ne.	
18	(3)(i) Residential furnaces and re	sidential boilers shall comply with	th the following Annual
19	Fuel Utilization Efficiency (AFUE) and e	lectricity ratio values.	
20	Product Type	Minimum AFUE	Maximum
21	electricity ratio		
22	Natural gas and propane fired furnaces	90%	
22 23	Natural gas and propane fired furnaces	90% 2.0%	
	Natural gas and propane fired furnaces Oil-fired furnaces>94,000		
23			
23 24	Oil-fired furnaces>94,000	2.0%	
232425	Oil-fired furnaces>94,000	2.0%	
23242526	Oil-fired furnaces>94,000 Btu/hour in capacity	2.0%	
2324252627	Oil-fired furnaces>94,000 Btu/hour in capacity Oil-fired furnaces>94,000	2.0% 83% 2.0%	
232425262728	Oil-fired furnaces>94,000 Btu/hour in capacity Oil-fired furnaces>94,000	2.0% 83% 2.0% 83% 2.3%	
23242526272829	Oil-fired furnaces>94,000 Btu/hour in capacity Oil-fired furnaces>94,000 Btu/hour in capacity	2.0% 83% 2.0% 83% 2.3%	Not
23 24 25 26 27 28 29 30	Oil-fired furnaces>94,000 Btu/hour in capacity Oil-fired furnaces>94,000 Btu/hour in capacity Natural gas and oil, and propane-fired hor	2.0% 83% 2.0% 83% 2.3%	Not
23 24 25 26 27 28 29 30 31	Oil-fired furnaces>94,000 Btu/hour in capacity Oil-fired furnaces>94,000 Btu/hour in capacity Natural gas and oil, and propane-fired howater residential boilers	2.0% 83% 2.0% 83% 2.3%	Not

2	(ii) The chief of energy and community services commissioner shall adopt rules to
3	provide for exemptions from compliance with the foregoing residential furnace or residential
4	boiler AFUE standards at any building, site or location where complying with said standards
5	would be in conflict with any local zoning ordinance, fire code, building or plumbing code or
6	other rule regarding installation and venting of residential furnaces or residential boilers. This
7	clause becomes effective if the state is granted a waiver from federal preemption to implement
8	the furnace standard.
9	(iii) The provisions of this subsection 39-27-5(b)(a)(3) shall be effective upon
10	determination by the chief of energy and community services that the same or substantial
11	corresponding standards have been enacted in two (2) New England states.
12	(4)(i) State regulated incandescent reflector lamps shall meet the minimum average lamp
13	efficacy requirements for federally regulated incandescent reflector lamps contained in 42 U.S.C.
14	§ 6295(i)(1)(A).
15	(ii) The following types of incandescent reflector lamps are exempt from these
16	requirements:
17	(I) lamps rated at fifty (50) watts or less of the following types: BR30, BR40, ER30 and
18	ER40;
19	(II) lamps rated at sixty-five (65) watts of the following types: BR30, BR40, and ER40;
20	and and
21	(III) R20 lamps of forty five (45) watts or less.
22	(5)(i) Walk-in refrigerators and walk-in freezers with the applicable motor types shown in
23	the table below shall include the required components shown.
24	MOTOR Type Required Components
25	All Interior lights: light sources
26	with an
27	efficacy of forty five (45)
28	lumens per
29	
30	losses
31	(if any). This efficacy standard
32	does not
33	apply to LED light sources until
34	January

1

applicable

	2010.
All	Automatic door closers that
firmly close	
	all reach in doors.
\ \ \ \ \ \ \ \ \ \ \ \ \ \	Automatic door closers that
firmly close	
	all walk-in doors no wider than
3.9 feet	
	and no higher than 6.9 feet that
nave	
	been closed to within one inch
of full	
	closure.
All	Wall, ceiling, and door
insulation at least	
	R-28 for refrigerators and at
least R 34 for	
	freezers
All	Floor insulation at least R-28 for
reezers	
	(no requirements for
refrigerators)	
Condenser fan motors of under one horsepower	Electronically commutated
motors,	
	Permanently split capacitor type
notors	
	Polyphase motors of one half
(1/2)	
	horsepower or more
Single phase evaporator fan motors of	Electronically commutated
notors	
under one horse power and less than four	
hundred sixty (460) volts	
(ii) In addition to the requirements in para	graph (i), walk in refrigerators and walk in

1	freezers with transparent reach in doors shall meet the following requirements: transparent reach-
2	in doors shall be of triple pane glass with either heat reflective treated glass or gas fill; if the
3	appliance has an anti-sweat heater without anti-sweat controls, then: the appliance shall have a
4	total door rail, glass, and frame heater power draw of no more than forty (40) watts if it is a
5	freezer or seventeen (17) watts if it is a refrigerator per foot of door frame width; and if the
6	appliance has an anti-sweat heater with anti-sweat heat controls, and the total door rail, glass, and
7	frame heater power draw is more than forty (40) watts if it is a freezer or seventeen (17) watts if it
8	is a refrigerator per foot of door frame width, then: the anti-sweat heat controls shall reduce the
9	energy use of the anti-sweat heater in an amount corresponding to the relative humidity in the air
10	outside the door or to the condensation on the inner glass pane.
11	(b) Not later than June 1, 2020, the commissioner, in consultation with the state building
12	commissioner shall adopt regulations, in accordance with the provisions of chapter 35 of title 42,
13	establishing minimum efficiency standards for the types of new products set forth in § 39-27-4(a).
14	The regulations shall provide for the following minimum efficiency standards:
15	(1) Air compressors that meet the twelve (12) criteria listed on pages 350 and 351 of the
16	"Energy Conservation Standards for Air Compressors" final rule issued by the U.S. Department
17	of Energy on December 5, 2016, shall meet the requirements in Table 1 on page 352 following
18	the instructions on page 353 and as measured in accordance with Appendix A through Subpart T
19	of Part 431 of Title 10 of the Code of Federal Regulations (CFR) "Uniform Test Method for
20	Certain Air Compressors" as in effect on July 3, 2017.
21	(2) Commercial dishwashers included in the scope of the ENERGY STAR Program
22	Requirements Product Specification for Commercial Dishwashers, Version 2.0, shall meet the
23	qualification criteria of that specification.
24	(3) Commercial fryers included in the scope of the ENERGY STAR Program
25	Requirements Product Specification for Commercial Fryers, Version 2.0, shall meet the
26	qualification criteria of that specification.
27	(4) Commercial steam cookers shall meet the requirements of the ENERGY STAR
28	Program Requirements Product Specification for Commercial Steam Cookers, Version 1.2.
29	(5) Computers and computer monitors shall meet the requirements of § 1605.3(v) of Title
30	20 of the California Code of Regulations (C.C.R.) and compliance with those requirements shall
31	be as measured in accordance with test methods prescribed in § 1604(v) of those regulations.
32	(i) The rules shall define "computer" and "computer monitor" to have the same meaning
33	as set forth in 20 C.C.R. § 1602(v).
34	(ii) The referenced portions of the C.C.R. shall be those adopted on or before the

1	effective date of this act. However, the commissioner shall have authority to amend the rules so
2	that the definitions of "computer" and "computer monitor" and the minimum efficiency standards
3	for computers and computer monitors conform to subsequently adopted modifications to the
4	referenced sections of the C.C.R.
5	(6) Faucets, except for metering faucets, and showerheads shall meet the standards shown
6	in this subsection when tested in accordance with Appendix S to Subpart B of Part 430 of Title 10
7	of the Code of Federal Regulations and compliance with those requirements shall be "Uniform
8	Test Method for Measuring the Water Consumption of Faucets and Showerheads" as in effect on
9	<u>January 3, 2017.</u>
10	(7) Lavatory faucets and replacement aerators shall not exceed a maximum flow rate of
11	one and five-tenths gallons per minute (1.5 gpm) at sixty pounds per square inch (60 psi).
12	(8) Residential kitchen faucets and replacement aerators shall not exceed a maximum
13	flow rate of one and eight-tenths gallons per minute (1.8 gpm) at sixty pounds per square inch (60
14	psi), with optional temporary flow of two and two-tenths gallons per minute (2.2 gpm), provided
15	they default to a maximum flow rate of one and eight-tenths gallons per minute (1.8 gpm) at sixty
16	pounds per square inch (60 psi) after each use.
17	(9) Public lavatory faucets and replacement aerators shall not exceed a maximum flow
18	rate of one-half gallon per minute (0.5 gpm) at sixty pounds per square inch (60 psi).
19	(10) Showerheads shall not exceed a maximum flow rate of two gallons per minute (2.0
20	gpm) at eighty pounds per square inch (80 psi).
21	(11) General service lamps shall meet or exceed a lamp efficacy of forty-five (45) lumens
22	per watt, when tested in accordance with the applicable federal test procedures for general service
23	lamps, prescribed in § 430.23(gg) of Title 10 of the Code of Federal Regulations as in effect on
24	<u>January 3, 2017.</u>
25	(12) High CRI fluorescent lamps shall meet the minimum efficacy requirements
26	contained in § 430.32(n)(4) of Title 10 of the Code of Federal Regulations as in effect on January
27	3, 2017, as measured in accordance with Appendix R to Subpart B of Part 430 of Title 10 of the
28	Code of Federal Regulations "Uniform Test Method for Measuring Average Lamp Efficacy (LE),
29	Color Rendering Index (CRI), and Correlated Color Temperature (CCT) of Electric Lamps" as in
30	effect on January 3, 2017.
31	(13) Urinals and water closets, other than those designed and marketed exclusively for
32	use at prisons or mental health facilities, shall meet the standards shown in this chapter when
33	tested in accordance with Appendix T to Subpart B of Part 430 of Title 10 of the Code of Federal
34	Regulations "Uniform Test Method for Measuring the Water Consumption of Water Closets and

1	Urinals" as in effect on January 3, 2017, and water closets shall pass the waste extraction test for
2	water closets (Section 7.10) of the American Society of Mechanical Engineers (ASME)
3	A112.19.2/CSA B45.1-2013.
4	(i) Wall-mounted urinals and floor-mounted urinals, except for trough-type urinals, shall
5	have a flush volume of five-tenths (0.5) of a gallon per flush.
6	(ii) Water closets, except for dual-flush tank-type water closets, shall have a maximum
7	flush volume of one and twenty-eight hundredths (1.28) of a gallon per flush.
8	(iii) Dual-flush tank-type water closets shall have a maximum dual flush effective flush
9	volume of one and twenty-eight hundredths (1.28) of a gallon per flush.
0	(14) Portable air conditioners shall have a Combined Energy Efficiency Ratio (CEER), as
1	measured in accordance with Appendix CC to Subpart B of Part 430 of Title 10 of the Code of
2	Federal Regulations "Uniform Test Method for Measuring the Energy Consumption of Portable
3	Air Conditioners" as in effect on January 3, 2017, that is greater than or equal to:
4	1.04 x SACC/(3.7117 x SACC ^{0.6384}) where SACC is Seasonally Adjusted Cooling
5	Capacity in Btu/h.
6	(15) Portable electric spas shall meet the requirements of the "American National
7	Standard for Portable Electric Spa Energy Efficiency" (ANSI/APSP/ICC-14 2014).
8	(16) Residential ventilating fans shall meet the qualification criteria of the ENERGY
9	STAR Program Requirements Product Specification for Residential Ventilating Fans, Version
20	<u>3.2.</u>
21	(17) Spray sprinkler bodies that are not specifically excluded from the scope of the
22	WaterSense Specification for Spray Sprinkler Bodies, Version 1.0, shall include an integral
23	pressure regulator and shall meet the water efficiency and performance criteria and other
24	requirements of that specification.
25	(18) Uninterruptible power supplies that utilize a NEMA 1-15P or 5-15P input plug and
26	have an AC output shall have an average load adjusted efficiency that meets or exceed the values
27	shown on page 193 of the pre-publication final rule "Energy Conservation Program: Energy
28	Conservation Standards for Uninterruptible Power Supplies" issued by the U.S. Department of
29	Energy on December 28, 2016, as measured in accordance with test procedures prescribed in
80	Appendix Y to Subpart B of Part 430 of Title 10 of the Code of Federal Regulations "Uniform
31	Test Method for Measuring the Energy Consumption of Battery Chargers" as in effect on January
32	<u>11, 2017.</u>
33	(19) Water coolers included in the scope of the ENERGY STAR Program Requirements
34	Product Specification for Water Coolers, Version 2.0, shall have on mode with no water draw

- energy consumption less than or equal to the following values as measured in accordance with the test requirements of that program:
- 3 (i) Sixteen hundredths kilowatt-hours (0.16 KWh) per day for cold-only units and cook
- 4 and cold units;

- 5 (ii) Eighty-seven hundredths kilowatt-hours (0.87 KWh) per day for storage type hot and
- 6 cold units; and
- 7 (iii) Eighteen hundredths kilowatt-hours (0.18 KWh) per day for on demand hot and cold
- 8 <u>units.</u>

39-27-6. Implementation.

- (a) No new commercial clothes washer, commercial pre-rinse spray valve, high intensity discharge lamp ballast, illuminated exit sign, low voltage dry type distribution transformer, torchiere, traffic signal module, or unit heater after January 1, 2007 may be sold or offered for sale in the state unless the efficiency of the new product meets or exceeds the efficiency standards set forth in the regulations adopted pursuant to § 39-27-5. No bottle-type-water dispenser, or commercial hot food holding cabinet, metal halide lamp fixture, single voltage external AC to DC power supply, state regulated incandescent reflector lamp, or walk in refrigerator or walk in freezer manufactured on or after January 1, 2008 may be sold or offered for sale in the state unless the efficiency of the new product meets or exceeds the efficiency standards set forth in the regulations adopted pursuant to § 39-27-5. No new automatic commercial icemaker, commercial refrigerator, refrigerator freezer, or freezer or large packaged air conditioning equipment manufactured on or after January 1, 2010 may be sold or offered for sale in the state unless the efficiency of the new product meets or exceeds the efficiency standards set forth in the regulations adopted pursuant to § 39-27-5.
- (b) No later than six (6) months after the effective date of this chapter, the chief of energy and community services, in consultation with the attorney general, shall determine if implementation of state standards for residential furnaces and residential boilers require a waiver from federal preemption. If the chief of energy and community services determines that a waiver from federal preemption is not needed, then no new residential furnace or residential boiler manufactured on or after January 1, 2008, or the date which is one year after the date of said determination, if later, may be sold or offered for sale in the state unless the efficiency of the new product meets or exceeds the efficiency standards set forth in the regulations adopted pursuant to § 39-27-5. If the chief of energy and community services commission determines that a waiver from federal preemption is required, then the chief of energy and community services commissioner may shall apply for such waiver within one year of such determination and upon

2	earliest date permitted by federal law.
3	(c) One year after the date upon which sale or offering for sale of certain products is
4	limited pursuant to this section, no new products may be installed for compensation in the state
5	unless the efficiency of the new product meets or exceeds the efficiency standards set forth in the
6	regulations adopted pursuant to § 39-27-5.
7	(d) On or after January 1, 2020, no new air compressor, commercial dishwasher,
8	commercial fryer, commercial steam cooker, computer or computer monitor, faucet, high CRI
9	fluorescent lamp, portable electric spa, residential ventilating fan, showerhead, spray sprinkler
10	body, uninterruptible power supply, urinal, water closet, or water cooler may be sold or offered
11	for sale, lease, or rent in the state unless the efficiency of the new product meets or exceeds the
12	efficiency standards provided in § 39-27-5.
13	(e) On or after January 1, 2022, no new portable air compressor may be sold or offered
14	for sale, lease, or rent in the state unless the efficiency of the new product meets or exceeds the
15	efficiency standards provided in § 39-27-5. This provision shall only apply if, prior to January 1,
16	2020, the Department of Energy (DOE) has not published a final rule in the Federal Register
17	establishing efficiency standards for portable air compressors and if, prior to January 1, 2022, the
18	rule has not been repealed, voided, or retracted.
19	(f) On or after February 1, 2022, no new portable air conditioner may be sold or offered
20	for sale, lease, or rent in the state unless the efficiency of the new product meets or exceeds the
21	efficiency standards provided in § 39-27-5. This provision shall only apply if, prior to January 1,
22	2019, the Department of Energy (DOE) has not published a final rule in the Federal Register
23	establishing efficiency standards for portable air conditioners and if, prior to February 1, 2022,
24	the rule has not been repealed, voided, or retracted.
25	(g) No later than January 1, 2020, and as necessary thereafter, the commissioner, in
26	consultation with the attorney general, shall determine which general service lamps are subject to
27	federal preemption. On or after January 1, 2020, no general service lamp that is not subject to
28	federal preemption may be sold or offered for sale in the state unless the efficiency of the new
29	product meets or exceeds the efficiency standards provided in § 39-27-5.
30	(h) One year after the date upon which the sale or offering for sale of certain products
31	becomes subject to the requirements of subsections (d), (e), (f), or (g) of this section, no such
32	products may be installed for compensation in the state unless the efficiency of the new product
33	meets or exceeds the efficiency standards provided in § 39-27-5.

approval of such waiver application, the applicable state standards shall go into effect at the

39-27-7. New and revised standards.

34

The commission commissioner may adopt regulations, in accordance with the provisions of chapter 35 of title 42, to establish increased efficiency standards for the products listed in § 39-27-4. In considering such amended standards, the commission commissioner, in consultation with the chief of energy and community services commissioner, shall set efficiency standards upon a determination that increased efficiency standards would serve to promote energy or water conservation in the state and would be cost-effective for consumers who purchase and use such products; provided, that increased efficiency standards shall become effective within one year following the adoption of any amended regulations establishing such increased efficiency standards. 39-27-8. Testing, certification, and enforcement. (a) The manufacturers of products covered by the chapter shall test samples of their products in accordance with the test procedures adopted pursuant to this chapter or those specified in the State Building Code. The chief of energy and community services commissioner, in consultation with the state building commissioner, shall adopt test procedures for determining the energy efficiency of the products covered by § 39-27-4 if such procedures are not provided for in this section, and § 39-27-5 of this chapter or in the State Building Code, except that the test procedure for: (1) Automatic commercial icemakers shall be the test standard specified by the Air Conditioning and Refrigeration Institute Standard 810-2003, as in effect on January 1, 2005; (2) Bottle type water dispensers shall be measured in accordance with the test criteria contained in version 1 of the U.S. Environmental Protection Agency's "Energy Star Program/Requirement for Bottled Water Coolers," except units with an integral, automatic timer shall not be tested using Section D, "Timer Usage," of the test criteria; (3) Commercial hot food holding cabinets shall be the "idle energy rate-dry test" on ASTM F2140-01, "Standard Test Method for Performance of Hot Food Holding Cabinets" published by ASTM International Interior volume and shall be measured in accordance with the method shown in the U.S. Commercial Hot Food Holding Cabinets as in effect on August 15, 2003; and (4) Residential furnaces and boilers AFUE shall be measured in accordance with the federal test method for measuring the energy consumption of furnaces and boilers contained in Appendix N to subpart B of part 430, title 10, Code of Federal Regulations. The chief of energy and community services shall use U.S. Department of Energy approved test methods, or in the absence of such test methods, other appropriate nationally recognized test methods. The chief of energy and community services commissioner may use

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

updated test methods when new versions of test procedures become available.

(b) Manufacturers of new products covered by § 39-27-4 of this chapter, except for single voltage external AC to DC power supplies, high intensity discharge lamp ballasts, walk in refrigerators and walk in freezers, shall certify to the chief of energy and community services commissioner that such products are in compliance with the provisions of this chapter. Such certifications shall be based on test results. The chief of energy and community services commissioner shall promulgate regulations governing the certification of such products and may coordinate with the certification programs of other states and federal agencies.

- (c) Manufacturers of new products covered by § 39-27-4 shall identify each product offered for sale or installation in the state as in compliance with the provisions of this chapter by means of a mark, label, or tag on the product and packaging at the time of sale or installation. The commissioner shall promulgate regulations governing the identification of such products and packaging, which shall be coordinated to the greatest practical extent with the labeling programs of other states and federal agencies with equivalent efficiency standards. The commissioner shall allow the use of existing marks, labels, or tags, which connote compliance with the efficiency requirements of this chapter.
- (c)(d) The chief of energy and community services commissioner may test products covered by § 39-27-4. If the products so tested are found not to be in compliance with the minimum efficiency standards established under § 39-27-5, the chief of energy and community services commissioner shall:
- 21 (1) Charge the manufacturer of such product for the cost of product purchase and testing; 22 and
 - (2) Make information available to the <u>attorney general and the</u> public on products found not to be in compliance with the standards.
 - (d)(e) With prior notice and at reasonable and convenient hours, the chief of energy and community services commissioner may cause periodic inspections to be made of distributors or retailers of new products covered by § 39-27-4 in order to determine compliance with the provisions of this chapter. The chief of energy and community services commissioner shall also coordinate in accordance with § 23-27.3-111.7 regarding inspections prior to occupancy of newly constructed buildings containing new products that are also covered by the State Building Code.
 - (e)(f) The chief of energy and community services commissioner shall investigate complaints received concerning violations of this chapter. Any manufacturer, distributor or retailer who violates any provision of this chapter shall be issued a warning by the chief of energy and community services commissioner for any first violation. Repeat violations shall be subject to

- a civil penalty of not more than two hundred fifty dollars (\$250) five hundred dollars (\$500).
- 2 Each violation shall constitute a separate offense, and each day that such violation continues shall
- 3 constitute a separate offense. Penalties assessed under this paragraph are in addition to costs
- 4 assessed under subsection (d) of this section.
- 5 SECTION 2. This act shall take effect upon passage.

LC001761

EXPLANATION

BY THE LEGISLATIVE COUNCIL

OF

AN ACT

RELATING TO PUBLIC UTILITIES AND CARRIERS -- THE ENERGY AND CONSUMER SAVINGS ACT OF 2005

This act would establish minimum energy and water efficiency standards for certain products sold or installed in the state.

This act would take effect upon passage.

LC001761